

NEW

EZstrip™

CT203/205 TR Muncher®



“Well proven member of the Muncher® family offering a more competitive solution to solids grinding maintenance”.

Capacity up to 440m³/h on raw sewage
up to 330m³/h on 4% sludge

Typical Applications

- Tanker reception
- Pump protection
- Fat/sludge conditioning

Pull back cutter stack

Allows removal of the cutter chamber for in-situ inspection without disturbing the inter-connecting pipework.

Inspection Parts

Offers easy inspection of the cutter stack assembly.

Low power

Rotational speed produces high torque, resulting in lower operating power at 1.5, 2.2 or 4kW, which are available with energy efficient motors.

Slow operational speed

Lower cutter tip speeds dramatically reduce wear rates. Slow speeds also ensure low noise and vibration, and good abrasion resistance.

PLC protection

Available with over-load protection to prevent serious damage to the Muncher®, saving on costly downtime.

Tanker reception

The off-loading requirements for ‘on-stand’ tankering are matched by the Muncher’s® capacity.

Flange connections

Standard 100-300mm with the option of Bauer quick release couplings.

Built-in trash trap

Catches any rejected material, which can then be removed through the access port.

Standardisation

Interchangeability of critical spares across the Muncher® range for all machines. Reduced level of stock holding.



One Company, Unlimited Solutions